## HP Jet Fusion 3D 4200 Printing Solution

Reinvent how you prototype and produce functional parts

Deliver quality output, up to 10 times faster<sup>1</sup> at half the cost.<sup>2</sup>

## Superior,<sup>3</sup> consistent part quality

- Gain control with advanced/custom print modes for mechanical/functional/aesthetic properties, accuracy, speed.
- Get truly functional parts with optimal mechanical properties<sup>4</sup> and monitor part quality during printing.
- Obtain predictable, reliable final printed parts that match your design.  $^{\rm 5}$
- Access new future materials and uncover new applications thanks to the HP Multi Jet Fusion Open Platform.

## **Breakthrough productivity**


- Produce more parts per day with continuous printing, fast cooling.<sup>1</sup>
- Streamline your workflow with HP's automated materials mixing and Processing Station.
- Cleaner experience with enclosed Processing Station and materials not classified as hazardous.<sup>6</sup>
- Rely on HP's world-class HP Jet Fusion 3D Solution Services to maximize uptime and productivity.

## Lower cost per part<sup>2</sup>

- Achieve half the cost per part<sup>2</sup> and reduce operational costs, opening your doors to short-run manufacturing.
- Benefit from a competitively priced 3D printing solution.<sup>2</sup>
- Optimize cost and part quality, with costefficient materials that offer industry-leading reusability.<sup>7</sup>
- Plan production times more accurately and predictably, to help increase your overall operational efficiency.
- Choose your ideal end-to-end solution from a range of printing and processing options.

For more information, please visit hp.com/go/3DPrint

## **HP Jet Fusion 3D 4200 Printing Solution**







## **HP Jet Fusion 3D 4200 Printing Solution**

Ideal for industrial prototyping and final part production environments producing 130-599 parts per week\*

# Reinventing 3D printing



Enabled by HP Jet Fusion 3D 4210/4200 Processing Station with Fast Cooling<sup>1</sup>



Rely on HP Jet Fusion 3D

## **HP services:**

Solution Services—including Next Business Day Support and Parts9-to help maximize uptime and productivity.



## **Ordering information**

Printer	M0P44B	HP Jet Fusion 3D 4200 Printer	
Accessories	MOP49C	HP Jet Fusion 3D 4200 Processing Station with Fast Cooling <sup>1</sup>	
	M0P45B	HP Jet Fusion 3D Build Unit	
	M0P54B	HP Jet Fusion 3D External Tank 5 units Bundle	
	M0P54D	HP Jet Fusion 3D External Tank Starter Kit	
Recommended accessories	Girbau DY130 Dyeing Solution <sup>11</sup>	Please consult with your local HP Partner First 3D Printing Specialist	
Original HP printheads	F9K08A	HP 3D600 Printhead	
Original HP agents	V1Q60A	HP 3D600 3L Fusing Agent	
	V1Q61A	HP 3D600 3L Detailing Agent	
	V1Q63A	HP 3D700 5L Fusing Agent	
	V1Q64A	HP 3D700 5L Detailing Agent	
Other supplies	V1Q66A	HP 3D600 Cleaning Roll	
Original HP 3D high reusability materials	V1R10A	HP 3D High Reusability PA 12 30L (13 kg) <sup>12</sup>	
	V1R16A	HP 3D High Reusability PA 12 300L (130 kg) <sup>12</sup>	
	V1R12A	HP 3D High Reusability PA 11 30L (14 kg) <sup>12, 13</sup>	
	V1R18A	HP 3D High Reusability PA 11 300L (140 kg) <sup>12, 13</sup>	
	V1R11A	HP 3D High Reusability PA 12 Glass Beads 30L (15 kg) <sup>12</sup>	
	V1R22A	HP 3D High Reusability PA 12 Glass Beads 300L (150 kg) <sup>12</sup>	
Materials Certified for HP Jet Fusion 3D Printing	EVNV1R14A	VESTOSINT <sup>®</sup> 3D Z2773 PA 12 30L (14 kg) <sup>12</sup>	
	EVNV1R17A	VESTOSINT® 3D Z2773 PA 12 300L (140 kg) <sup>12</sup>	
HP Jet Fusion 3D	U9ZS7E	HP Ready To Print Service	
Solution Services	U9EL9E	HP Installation w/Introduction to Basic Operation SVC for HP Jet Fusion 3D Processing Station with FC	
	1MZ23B	HP 3D Printer Initial Maintenance Kit	
	1MZ24A	HP 3D Printer Yearly Maintenance Kit	
	1MZ25B	HP 3D Post Processing Maintenance Kit	
	U9EK7E	HP Advanced Operation Training Service for Jet Fusion 3D Printer (HP Training Center)	
	U9EK4E	HP 3 year NBD* Onsite Hardware Support with DMR**	
	U9EQ8E	HP 3 year NBD* Onsite Build Unit Support	
	U9EM5E	HP 3 year NBD* Onsite Support for Processing Station with Fast Cooling	
	U9TZ7E	HP 3 year Shared HW Support, Parts NBD* with DMR** and 2 onsite visits for Printer	
	U9UA2E	HP 3 year Shared Hardware Support, Parts NBD* and 2 onsite visits for Build Unit	
	U9UA7E	HP 3 year Shared Hardware Support, Parts NBD* and 2 onsite visits for Processing Station with Fast Cooling	
	U9UB1E	HP Train to Maintain Service for Jet Fusion 3D Printer***	
	U9ZS9E	HP Uptime Kit for Jet Fusion 3D Printer***	
	U9ZT1E	HP Uptime Kit for Jet Fusion 3D Processing Station***	
	U9ZTOE	HP Uptime Kit for Jet Fusion 3D Build Unit***	
	U9VS9E	HP Upgrade to HP Jet Fusion 3D 4210 Printer Hardware Service	
	U9VT0E	HP Upgrade to HP Jet Fusion 3D Processing Station with Fast Cooling 4210 Hardware Service	

\* Next Business Day \*\* Defective Media Retention \*\*\* This is only for Shared Hardware Support Services

## **Technical specifications**<sup>14</sup>

## HP Jet Fusion 3D 4200 Printer

Printer	Technology	HP Multi Jet Fusion technology	
performance	Effective building volume	380 x 284 x 380 mm (15 x 11.2 x 15 in)	
	Building speed	4115 cm <sup>3</sup> /hr (251 in <sup>3</sup> /hr) <sup>15</sup>	
	Layer thickness	0.08 mm (0.003 in)	
	Print resolution (x, y)	1200 dpi	
Dimensions (w x d x h)	Printer	2210 x 1200 x 1448 mm (87 x 47 x 57 in)	
	Shipping	2300 x 1325 x 2068 mm (91 x 52 x 81 in)	
	Operating area	3700 x 3700 x 2500 mm (146 x 146 x 99 in)	
Weight	Printer	750 kg (1653 lb)	
	Shipping	945 kg (2083 lb)	
Network <sup>16</sup>	Gigabit Ethernet (10/100/1000Base-T), supporting the following standards: TCP/IP, DHCP (IPv4 only), TLS/SSL		
Hard disk	2TB (AES-256 encrypted, FIPS 140, disk wipe DoD 5220M)		
Software	Included software	HP SmartStream 3D Build Manager, HP SmartStream 3D Command Center	
	Supported file formats	3MF, STL	
	Certified third-party software	Autodesk <sup>®</sup> Netfabb <sup>®</sup> Engine for HP, Materialise Magics with Materialise Build Processor for HP Multi Jet Fusion, Siemens NX AM for HP Multi Jet Fusion	
Power	Consumption	9 to 11 kW (typical)	
	Requirements	Input voltage three phase 380-415 V (line-to-line), 30 A max, 50/60 Hz / 200-240 V (line-to-line), 48 A max, 50/60Hz	
Certification	Safety	IEC 60950-1+A1+A2 compliant; United States and Canada (UL listed); EU (LVD and MD compliant, EN60950-1, EN12100-1, EN60204-1, and EN1010)	
	Electromagnetic	Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACMA), New Zealand (RSM)	
	Environmental	REACH	
Warranty & Service coverage included	One-year limited hardware warranty		

#### HP Jet Fusion 4200 Processing Station with Fast Cooling<sup>1</sup>

Features	Automated mixing, sieving, and loading; semi-manual unpacking; fast cooling;' external storage tank			
Dimensions (w x d x h)	Processing station with fast cooling <sup>1</sup>	2990 x 934 x 2400 mm (117.7 x 36.8 x 94.5 in)		
	Shipping	3499 x 1176 x 2180 mm (137.8 x 46.3 x 85.8 in)		
	Operating area	3190 x 2434 x 2500 mm (125.6 x 95.8 x 99 in)		
Weight	Processing station with fast cooling <sup>1</sup>	480 kg (1058 lb)		
	Loaded	810 kg (1786 lb)		
	Shipping	620 kg (1367 lb)		
Power	Consumption	2.6 kW (typical)		
	Requirements	Input voltage single phase 200-240 V (line-to-li- ne), 19 A max, 50/60Hz or 220-240 V (line-to-neu- tral), 14 A max, 50Hz		
Certification	Safety	UL 2011, UL508A, NFPA, C22.2 NO. 13-14 compliant; United States and Canada (UL listed); EU (MD compliant, EN 60204-1, EN 12100-1 and EN 1010)		
	Electromagnetic	Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia (ACMA), New Zealand (RSM)		
	Environmental	REACH		
Warranty & Service coverage	One-year limited hardware warranty			

included

Eco Highlights

- Powders or agents are not classified as hazardous<sup>6</sup>
- Cleaner, more comfortable workplace—enclosed printing system, and automatic powder management<sup>6</sup>
- Minimizes waste due to industry-leading reusability of powder<sup>10</sup>
- Take-back program for printheads<sup>17</sup>

Find out more about HP sustainable solutions at hp.com/ecosolutions

Dynamic security enabled printer. Only intended to be used with cartridges using an HP original chip. Cartridges using a non-HP chip may not work, and those that work today may not work in the future. More at: hp.com/go/learnaboutsupplies.

#### For more information, please visit hp.com/go/3DPrint













- 1. Fast cooling is enabled by HP Jet Fusion 3D Processing Station with Fast Cooling and is recommended only for HP 3D High Reusability PA 12 and HP 3D High Reusability PA 12 Glass Beads. HP Jet Fusion 3D Processing Station with Fast Cooling accelerates parts cooling time versus recommended manufacturer time of selective laser sintering (SLS) printer solutions from \$100,000 USD to \$450,000 USD, as tested in April, 2016. Fused deposition modeling (FDM) not applicable. Continuous printing requires an additional HP Jet Fusion 3D Build Unit (standard printer configuration includes one HP Jet Fusion 3D Build Unit). Based on internal testing and simulation, HP Jet Fusion 3D average printing time is up to 10 times faster than average printing time of comparable FDM and SLS printer solutions from \$100,000 USD to \$300,000 USD on market as of April, 2016. Testing variables for the HP Jet Fusion 4210/4200 Printing Solutions: Part quantity: 1 full build chamber of parts from HP Jet Fusion 3D at 20% of packing density versus same number of parts on above-mentioned competitive devices; Part size: 30 cm<sup>3</sup>; Layer thickness: 0.08 mm/0.003 inches.
- 2. Based on internal testing and public data, HP Jet Fusion 3D 4200 Printing Solution average printing cost per part is half the average cost of comparable fused deposition modeling (FDM) and selective laser sintering (SLS) printer solutions from \$100,000 USD to \$300,000 USD on market as of April, 2016. Cost analysis based on: standard solution configuration price, supplies price, and maintenance costs recommended by manufacturer. Cost criteria: printing 1 build chamber per day/5 days per week over 1 year of 30 cm<sup>3</sup> parts at 10% packing density using HP 3D High Reusability PA 12 material, and the powder reusability ratio recommended by manufacturer.
- 3. Based on HP's unique multi-agent printing process. Excellent dimensional accuracy and fine detail within allowable margin of error. Based on dimensional accuracy of ±0.2 mm/0.008 inches on XY for hollow parts below 100 mm/3.94 inches and ±0.2% for hollow parts over 100 mm/3.94 inches, using HP 3D High Reusability PA 12 material, measured after sandblasting. See <u>hp.com/go/3Dmaterials</u> for more information on materials specifications.
- Based on the following mechanical properties: Tensile strength at 48 MPa (XYZ), Modulus at 1700-1800 MPa (XYZ). ASTM standard tests with HP 3D High Reusability PA 12 material. See <u>hp.com/</u> go/3Dmaterials for more information on materials specifications.
- 5. Within allowable margin of error. Based on dimensional accuracy of ±0.2 mm/0.008 inches on XY for hollow parts below 100 mm/3.94 inches and ±0.2% for hollow parts over 100 mm/3.94 inches, using HP 3D High Reusability PA 12 material, measured after sandblasting. See <u>hp.com/go/3Dmaterials</u> for more information on materials specifications.

- 6. Compared to manual print retrieval process used by other powder-based technologies. The term "cleaner" does not refer to any indoor air quality requirements and/or consider related air quality regulations or testing that may be applicable. The HP powder and agents do not meet the criteria for classification as hazardous according to Regulation (EC) 1272/2008 as amended.
- Industry-leading surplus powder reusability based on using HP 3D High Reusability PA 12 at recommended packing densities and compared to selective laser sintering (SLS) technology, offers excellent reusability without sacrificing mechanical performance. Tested according to ASTM D638, ASTM D256, ASTM D790, and ASTM D648 and using a 3D scanner for dimensional accuracy. Testing monitored using statistical process controls.
- 8. For advanced data features charges may apply in the future.
- 9. Available in most countries, subject to Terms & Conditions of HP Limited Warranty and/or Service Agreement. Please consult your local sales representatives for further details.
- 10. HP Jet Fusion 3D printing solutions using HP 3D High Reusability PA 12 and HP 3D High Reusability PA 11 provide 80% post-production surplus powder reusability, producing functional parts batch after batch. For testing, material is aged in real printing conditions and powder is tracked by generations (worst case for recyclability). Parts are then made from each generation and tested for mechanical properties and accuracy.
- 11. This product will be available in Europe in August 2018, and in the Americas in September 2018.
- 12. Liters refers to the materials container size and not the actual materials volume. Materials are measured in kilograms.
- 13. Available in the second half of 2018.
- 14. For latest technical specifications, please visit hp.com/go/3DPrint.
- 15. Based on 0.08-mm (0.003-in) layer thickness and 7.55 sec/layer.
- 16. The HP Jet Fusion 3D Printing Solution should be connected to the HP Cloud in order to enable the correct functioning of the printer and to offer better support.
- 17. Printing supplies eligible for recycling vary by printer. Visit <u>hp.com/recycle</u> to see how to participate and for HP Planet Partners program availability; program may not be available in your area. Where this program is not available, and for other consumables not included in the program, consult your local waste authorities on appropriate disposal.

#### Learn more about HP Multi Jet Fusion technology at

hp.com/go/3DPrint Connect with an HP 3D Printing expert or sign up for the latest news about HP Jet Fusion 3D Printing: hp.com/go/3Dcontactus

© Copyright 2016, 2018 HP Development Company, L.P.

The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

